







## The QuakeFinder Earthquake Forecasting Process

Electromagnetic Signals:

Magnetic Pulses

Air Conductivity

Infrared

Tom Bleier, Clark Dunson

QuakeFinder

## **Topics**

- What is QuakeFinder?
- QF instruments
- Examples of "quiet days" and "pre-earthquake" days
- Simultaneous 3 indicator "patterns"
- QF and Partner Networks
- How the data is ingested and quality checked
- How QF algorithms work today
- QF "process" of checks and balances to reduce false alarms
- Current "challenges" handling ambient noise

#### <u>Future</u> options being considered:

Documenting Future (QF) "Forecasts" with CSEP
 with Time, Distance, Magnitude, Confidence Levels

#### What is QuakeFinder?

- Stellar Solutions: Satellite Sys. Engineering Co.
- Humanitarian R&D Division: QuakeFinder
  - Give back to Community
  - Mission/Goal: To save lives by forecasting major earthquakes
  - Develop EM Techniques for Short Term Forecasts
    - Days to Weeks
    - Data Provider to Gov.
  - Funded by Stellar Solutions
    - Supplemented by NASA ES, PG&E, Telefonica, Musk, Vodafone

#### QuakeFinder Instruments (Ver. 6)


- 3 Axis Induction Magnetometers
  - 0.1pT at 1 Hz noise floor, 24 bit A/D
- Positive and Negative ion sensors
  - 10^6 ions/cc/sec range
  - 500 ions/cc/sec resolution
- 60MB data per day thru Cell
  - Solar Powered or 120/240 VAC
- Instrument for Noise:
  - Rel. Humidity, geophone






# Examples of "Quiet Days" and "Pre-Earthquake" Days


24 Hr Time Series: Pulses



#### Air Conductivity




**Pulse Counts** 




32 Days

## Simultaneous 3 indicator "patterns"

#### Alum Rock M5.4




#### **QuakeFinder and Partner Networks**







## **Data Ingest and Quality Checks**



## **QF Automated Algorithms**

Pulse Counts (3-5 levels) Azimuth Pulses

**Direction of Arrival** 

#### Ion Limits (in work)

Dirty sensor?

Humidity >95%

Pos or Neg?

Pattern reasonable?

#### IR Night Time Slopes

Reasonableness


**Cloud Masking** 

Temp, adjacent pixels, confidence

**Pixel Registration** 

Ground tie points








Ion

875

## **QF Data Validity Process**

- What if we do see 1,2,3 Interesting Patterns?
  - Are they simultaneous per the "template"?
  - Manually Look at Raw Data
    - Check waveforms (a new type of noise?)
  - Check Automated Limit values
  - Check Pulses against Lightning Tables
    - EarthNetworks (soon to be automated)
  - Call Homeowner at Site
    - Is there some activity there? (plowing, pumps, traffic)

#### **Current "Challenges" Handling Ambient Noise**



#### Documenting Future (QF) "Forecasts" w/ CSEP

(Proposed---No forecasts made yet)

Activity noticed ("Exception" to limits or manual viewing)

- If Data Quality is good AND If Noise is understood
  - Checked with homeowner for unusual activity
- If Pulses are high for 3-5 days (30% confidence)-tbd
- If Pulse Azimuth is "clustering" (20% confidence)
- If <u>Positive Ion</u> sensor is high (20% confidence)
  - Greater than 5 hrs (AND after pulse high span)
  - No high Humidity or dirty plates
- If IR shows Slope > 0 at same area/site (10% confidence)
  - Several pixels, no clouds nearby
- Are other EM researchers observing signals in same area? ++

#### What would a Forecast look like?

- Location: Within 30km of site location
- Time: Within 12-48 hrs of ion spike start
- Magnitude:
  - Depends on pulse pattern (energy levels, days)
  - Number of sites detecting pulses (1,2,3 sites)
- Confidence (additive as shown before)